



WATERLOO NORTH HYDRO INC.

METERING SPECIFICATIONS

EFFECTIVE:

May 1, 2021

Revision 3

Approved by:

DMoryc

Dorothy Moryc, P.Eng.
VP of Engineering, Stations, and Metering

Certificate of Approval

The installation work covered by this document meets the
safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021.
Date

DMoryc, P.Eng.
Signature & Professional Designation

See Waterloo North Hydro Inc. web site for the latest revisions at www.wnhydro.com. Comments on this document can be e-mailed to Customersupport@wnhydro.com or mailed to Customer Service at 526 Country Squire Road, Waterloo ON N2J 4G8. These specifications are for use only by Customers within the WNHI service territory. This document does not replace notification and communication requirements for servicing. Waterloo North Hydro Inc.'s liability to any person is limited to damages that arise directly out of the negligence or the willful misconduct of WNHI.



METERING SPECIFICATIONS

Document History

| Revision | Description | Date | Approvals |
|-----------------|---|--------------|---|
| 0 | Original Issue | June 2, 2008 | Herbert Haller P.Eng VP, Engineering & Stations |
| 1 | Revision to Update Ganged Meter Base Part Number in Table 2 | May 21, 2009 | Erik Veneman, P.Eng. Manager of Distribution Engineering |
| 2 | ESA Certificate of Approval Added | June 2, 2011 | Herbert Haller P.Eng VP, Engineering & Stations |
| 3 | Specification drawings Updated | May 1, 2021 | Dorothy Moryc, P.Eng. VP, Engineering & Stations |



TABLE OF CONTENTS

| | |
|--|-----------|
| <i>Preface</i> | 4 |
| 1. RESPONSIBILITIES | 5 |
| 1.1 WATERLOO NORTH HYDRO INC. | 6 |
| 1.2 THE CUSTOMER | 6 |
| 2. GENERAL | 7 |
| 2.1 ACCESS | 8 |
| 2.2 LOCATION | 9 |
| <i>Outdoor:</i> | 9 |
| <i>Indoor:</i> | 9 |
| 2.3 TECHNICAL REQUIREMENTS | 9 |
| 2.4 METER ROOMS | 10 |
| 2.5 SERVICE IDENTIFICATION | 11 |
| 3. EQUIPMENT REQUIREMENTS | 12 |
| 3.1 SINGLE-PHASE SERVICES UP TO AND INCLUDING 200A | 13 |
| 3.2 SINGLE PHASE SERVICES ABOVE 200A | 13 |
| 3.3 MULTI-UNIT SITES | 13 |
| 3.4 THREE PHASE SERVICES | 14 |
| 3.5 CENTRAL METERING | 15 |
| 3.6 PRIMARY METERING | 16 |
| 3.7 INTERVAL METERING | 17 |
| 3.8 GENERATION METERING | 17 |
| <i>Net Metering</i> | 17 |
| <i>IESO Contracted Generators Micro FIT and FIT</i> | 17 |
| <i>Load Displacement Generators:</i> | 18 |
| <i>Emergency Backup Generators</i> | 18 |
| 3.9 PULSE OUTPUTS | 18 |
| 3.10 FIRE EQUIPMENT CONNECTION | 19 |
| 4. APPENDICIES | 20 |
| APPENDIX 'A' | 21 |
| METERING STANDARDS DRAWINGS | 21 |
| APPENDIX 'B' | 23 |
| WNH APPROVED METER BASES | 23 |
| APPENDIX 'C' | 24 |
| WNH APPROVED COMBINATION TRANSFER SWITCH METER BASES & PLUG-IN TRANSFER DEVICES | 24 |
| APPENDIX 'D' | 25 |
| METERING PULSE OUTPUT(S) ACCESS AGREEMENT | 25 |



Preface

This specification prescribes the requirements for Waterloo North Hydro Inc. (WNHI), metering equipment installation. It is the Customer's and their Electrician/Contractor's responsibility to familiarize themselves with these specifications.

WNHI reserves the right to refuse to energize any part of the electrical plant that does not conform to these specifications. WNHI assumes no responsibility whatsoever for the cost of repairs, or delays in energizing the system incurred as a result of disregarding these specifications.

The latest edition of the Ontario Electrical Safety Code shall apply unless otherwise stated in these specifications. The Customer and its agents are to familiarize themselves with, and abide by, all relevant Provincial Statutes and Municipal By-Laws. Such relevant regulations include in part, the Occupational Health and Safety Act and Regulations for Construction Projects. Also applicable are Region of Waterloo, City of Waterloo and Township of Woolwich and Wellesley By-Laws.

WNHI is regulated by the Ontario Energy Board (OEB) and complies with Section 3 of the Distribution System Code, which outlines the requirements for connections and expansions.

Section 1 of these Metering Specifications provides general WNHI and Customer responsibilities. Sections 2 and 3 provide technical requirements. Also included are drawings and tables providing additional detailed information. Additional metering requirements are listed in the OEB's Distribution System Code. Metered Market Participants in the Independent Electricity System Operator (IESO) administered wholesale market must meet or exceed all IESO metering requirements.

In all cases, the Customer shall consult with WNHI prior to the start of work to determine specific metering requirements. Meters shall not be installed unless all applicable requirements have been met.



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

1. RESPONSIBILITIES



1.1 Waterloo North Hydro Inc.

- 1.1.1 WNHI shall supply and maintain revenue meters, instrument transformers (IT's), interconnecting wiring, ancillary devices, secondary wiring, seals, and other related equipment for revenue metering in a timely manner and in compliance with applicable legislation, WNHI's Metering Specifications, and WNHI's Conditions of Service.

1.2 The Customer

- 1.2.1 The Customer shall comply with these specifications for each type of electrical service listed, WNHI's Conditions of Service and all applicable legislation.
- 1.2.2 Detailed power riser diagrams and drawings showing the metering provision and arrangement for all commercial services shall be submitted to WNHI for approval before construction begins.
- 1.2.3 Prior to issuing a Service Order to have the metering equipment installed and the service energized, the Customer must contact WNHI's Customer Service Department and open a new account.



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

2. GENERAL



METERING SPECIFICATIONS

2.1 Access

- 2.1.1 WNHI shall have access to Customer property to install, read, and maintain its metering equipment, in accordance with these requirements and Section 40 of the Electricity Act.
- 2.1.2 The Customer must provide or arrange free, safe and unobstructed access during regular business hours to any authorized representative of WNHI for the purpose of meter reading, meter changing, or meter inspection. Where premises are closed during WNHI's normal business hours, the Customer must, on reasonable notice, arrange such access at a mutually convenient time.
- 2.1.3 The Customer shall be responsible for supplying a key to WNHI. WNHI may request that the lock be keyed to WNHI specifications. In specific instances and at the sole discretion of WNHI, the requirement for an outside door may be waived.
- 2.1.4 If the metering equipment is located on a mezzanine, there must be a proper stairway which is compliant with applicable building and safety regulations, including a handrail that leads to the location
- 2.1.5 No person, except those authorized by WNHI, may remove, connect, or otherwise interfere with WNHI's meters, wires, ancillary equipment or seals. The Customer shall be responsible for the care and safekeeping of WNHI meters, wires and ancillary equipment on the Customer's premises. For deliberate damage or negligence of WNHI equipment, other than by ordinary wear and tear, wind or lightning, the Customer shall be liable to pay to WNHI the value of such equipment, or at the option of WNHI, the cost of repairing the same.
- 2.1.6 An adequate working space in front of equipment, with a radius not less than 1m (39") and minimum ceiling height of 2.1m (83") for the full width of the installation shall be maintained at all times. The floor surface shall be solid and flat with no more than five (5°) degree slope. This space shall not be used for storage, etc. Noticeable, repetitive obstruction of this working space can be remedied by WNHI notifying the Fire Department and Electrical Safety Authority.
- 2.1.7 Unobstructed working space in front of equipment shall be maintained, free from or protected against, the adverse effects of moving machinery, vibration, dust, moisture or fumes.
- 2.1.8 Metering equipment shall not be located in space that could become a confined space.
- 2.1.9 Any compartments, cabinets, boxes, sockets, or other workspace provided by the Customer for the installation of WNHI's metering equipment shall be for the exclusive use of WNHI. No equipment, other than that provided and installed by WNHI, may be installed in any part of the WNHI metering workspace.
- 2.1.10 Where excessive vibration may affect or damage WNHI metering equipment, adequate shock absorber mounting suitable to WNHI shall be provided and installed by the Customer. The Customer or their contractor shall contact WNHI when there is the possibility that such conditions may occur.
- 2.1.11 Where there is the possibility of danger to WNHI employees or damage to equipment from moving machinery, dust, fumes, moisture, vandalism etc., protective arrangements satisfactory to WNHI and the Electrical Safety Authority shall be made.
- 2.1.12 All site installations shall be considered as "Safe Work Site Areas". A safe work site area shall be determined when the meter installer is on location. If a work site is deemed unsafe or there are safety concerns by the installer, the installation of the meter shall not proceed until appropriate remedies are put in place.
- 2.1.13 If, in the sole opinion of WNHI, building additions, alterations, fencing, tree growth or other obstruction, etc. render the meter inaccessible for reading and/or servicing, the meter shall be relocated to a WNHI approved location at the Customer's expense. Where such a condition exists, the Customer shall be granted 30 days to relocate the meter or ensure suitable access.



2.2 Location

- 2.2.1 All meters and meter cabinets shall be mounted level in the horizontal and vertical planes.
- 2.2.2 Meters are to be mounted at a height of 1.6m (5'-8") \pm 100mm (4") when measured from finished grade to the center of the meter face/glass.

Outdoor:

- 2.2.3 Meter bases shall be mounted on the exterior of the building within 3m (10') of the front corner of the building. The front of the building is that side which is the closest point of supply as determined by WNH's Engineering Department.
- 2.2.4 No part of the meter base is permitted to be above central air conditioners, window wells or any obstacles that prevent access to the meter.
- 2.2.5 No part of the meter base is permitted within 1m of a gas meter.
- 2.2.6 A temporary finished grade may be permitted only if the meter installer agrees the grade is acceptable and the surface area is safe to work on. This temporary grade condition must still meet the terms of item 2.2.1 and 2.2.2. This is only a temporary condition until final grading can be completed. The permanent finished grade should not be altered in any way after the meter has been installed.
- 2.2.7 All metering cabinets and enclosures that are located outdoors shall be stainless steel and have a minimum NEMA 3R outdoor rating.

In specific instances and at the sole discretion of WNH, a separate meter base enclosure may be requested to protect against vandalism or harsh environmental conditions.

Indoor:

- 2.2.8 If a metering center is used, the minimum height allowed for the bottom row of meters is 610mm (24") and the maximum height allowed for the top row of meters is 1.7m (5'6") \pm 150mm (6") as shown in drawing "MS-20B". Both dimensions are measured from finished floor elevation to the center of the meter face/glass.
- 2.2.9 Metering cabinets, if required, shall be mounted at 1.83m (6') \pm 50mm (2") with the exception of a 1200mm x 1200mm x 300mm (48" x 48" x 12") meter cabinet which shall be mounted at 1.98m (6'6") \pm 50mm (2") from the finished floor elevation to the top of the metering cabinet. All cabinets to be mounted with the right door opening first.
- 2.2.10 The Customer's main switch shall be installed so that the top of the switch is 1.83m (6') or less from the finished floor elevation. The Customer's main switch shall permit the sealing and padlocking of the handle in the "open" position and the cover or door in the "closed" position.

2.3 Technical Requirements

- 2.3.1 Metering will typically be installed on the low voltage side of the WNH or Customer owned transformer (secondary metering). Primary metering may be provided at the discretion of WNH. For primary metering details, refer to Section 3.6.
- 2.3.2 In order to preserve the integrity and accuracy of WNH's metering systems, no devices other than those required for WNH's purposes shall be permitted to be connected to the metering circuits. Any metering or load control equipment required by the Customer must be connected to the Customer's own current and voltage transformers, which must be installed on the load side of WNH's metering equipment. Any secondary arresters, power factor correction capacitors, ground fault indicator lights or other Customer



equipment must also be connected on the load side of WNHI's metering equipment. All Customer connections shall be made to the load side of WNHI's metering.

- 2.3.3 Customer owned metering or load control equipment cannot be installed in the same metering cabinet or metering switchgear cell, as those of WNHI.
- 2.3.4 The Customer is required to supply, install and maintain an ESA compliant and WNHI approved meter base for the use of WNHI's self-contained socket meters. For the current list of approved meter bases, refer to Appendix B.
- 2.3.5 All meter bases must be equipped with tunnel type lugs on the line side for termination of WNHI's copper or aluminum conductors and be equipped with a with a dielectric cover and security ring.
- 2.3.6 Any conduits for the exclusive use of WNHI metering circuits shall have no more than three 90° bends. No fittings with removable covers are permitted. The Customer or Contractor shall install nylon or a poly rope pull line in the conduit with an excess of 200mm (8") loop left at each end.
- 2.3.7 Meter bases for use on Commercial/Industrial installations shall be installed on the load side of the Customer's main switch and located indoors. The Customer is required to supply and install a 5-jaw or 7-jaw, CSA approved meter socket. Where a neutral connection to the meter socket is required, it shall be not less than #12 AWG copper or equivalent and made directly to the neutral bus.
- 2.3.8 In specific instances and at the sole discretion of WNHI, the main disconnect and metering for Commercial/Industrial installations may be approved to be located outdoors. If outdoor metering is approved, the meter cabinet must be constructed of stainless steel and have a minimum NEMA 3R outdoor enclosure rating.
- 2.3.9 Barriers are required in each section of switchgear or service entrance equipment between metered cell and all adjacent cells.
- 2.3.10 Side-hinged doors shall be installed over all live electrical equipment where WNHI personnel may be required to work (i.e. line splitters, un-metered sections of switchgear, breakers, switches, metering compartments, meter cabinets and enclosures). These hinged doors shall have metal latch with provision for sealing and padlocking. Where bolts are used, they shall be of the captive knurled type. All outer-hinged doors shall open no less than 135°. All inner-hinged doors shall open to a full 90°.
- 2.3.11 Each detached, semi-detached or row housing unit (freehold or condominium) shall be separately metered by a meter that is located outside. For condominium row housing, all meter bases for each block must be installed using WNHI approved meter bases located on one end of each block (as per the design drawing). The Customer shall be responsible for the extension of the unit services from the meter to the individual units. The individual units must be numbered and identified in accordance with Section 2.5 and drawing "MS-1". Refer to Section 3.3 for further details on multi-unit metering.
- 2.3.12 Meters for new or upgraded residential services shall be mounted outdoors on a meter base approved by WNHI. See Appendix B.
- 2.3.13 When a residential Customer is upgrading their service capacity, and the meter is inside, it must be moved outside to a WNHI approved location at the Customer's expense.

2.4 Meter Rooms

- 2.4.1 Meter rooms shall be located on the main floor of the building and accessible to WNHI via an outside lockable door at grade level. The minimum door dimensions shall be 2000mm x 810mm (6'8" x 2'8"). The Customer shall be responsible for supplying a key to WNHI. WNHI may request that the lock be keyed to WNHI specifications.
- 2.4.2 Lighting levels of at least 6 lux (65-foot candles) shall be maintained.
- 2.4.3 No water, gas, sewer, or other pipes, communications wire or equipment shall be permitted to encroach



on the safe working space requirements, as viewed by WNHI, of the metering equipment. Where a meter room is provided, no items near the room can present a hazard to WNHI employees.

- 2.4.4 In specific instances and at the sole discretion of WNHI, the requirement for an outside door may be waived (i.e. a high rise apartment building where meter rooms may be required to be located on more than one floor).

2.5 Service Identification

- 2.5.1 Customers shall permanently and legibly identify all metered services with respect to unit number and/or civic address. The units, meter bases and main panel disconnect switches must have permanent unit numbers installed prior to the installation of any metering apparatus according to drawing "MS- 1".
- 2.5.2 The Customer must inform WNHI in writing if changes are made to unit numbering and shall be liable to pay WNHI any incurred costs as a result of unit re-numbering.



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

3. EQUIPMENT REQUIREMENTS



3.1 Single-Phase Services Up to and Including 200A

- 3.1.1 For metering locations and servicing details, refer to drawing "MS-10A".
- 3.1.2 Each detached, semi-detached or linear row-housing unit shall be separately metered.

3.2 Single Phase Services Above 200A

3.2.1 225A to 400A single phase service requirements:

- a) Use of a WNHI approved transformer-rated combination meter base. Refer to drawing "MS-10D" for installation details and Appendix B for approved meter bases.
- b) Customer to supply and install combination meter base enclosure outside complete with lugs for conductor terminations on both sides of the WNH supplied Current Transformer (CT). Customer shall be responsible for load side conductor termination and line side conductor termination (if Customer owned conductor) inside the meter base.
- c) The 5-jaw meter base must be equipped with an automatic bypass for the current circuit on the left side, with the 5th-jaw located at the 9 o'clock position and equipped with a stainless steel security ring.

3.2.2 225A to 600A single phase service requirements:

- a) See section 3.5 for central metered service (CMS) services.
- b) For indoor services Customer shall supply and install 900mm x 900mm x 300mm (36"x36"x12") metering cabinet and WNHI approved 5-jaw meter base. Refer to drawings "MS-2 and MS-10F" for installation details and Appendix B for approved meter bases. If a Customer requires a greater service size than 600 amperes, single-phase, they will be required to convert to a three-phase service, at their expense.

3.3 Multi-Unit Sites

- 3.3.1 The Customer or a representative must be present at the time of the meter installation and assist in the verification of each unit. The Metering Department at WNHI needs to be notified at least 5 working days in advance to arrange a day and time (during normal working hours) to meet on site.
- 3.3.2 The Customer and/or electrician shall provide WNHI with the following, prior to the service being energized:
 - a) All keys required to gain access to the electrical and metering rooms
 - b) A copy of the building layout, indicating the municipal address and permanent unit numbers, for each floor if applicable, duly signed by the electrician or developer as correct.
 - c) A copy of the meter panel layout, indicating the correct corresponding permanent unit numbers, for each floor if applicable, duly signed by the electrician or developer as correct.
- 3.3.3 The units, doors, meter bases and main disconnect switches must have permanent unit numbers installed prior to the installation of any metering apparatus according to drawing "MS-1".
- 3.3.4 Examples of the equipment layout for multi-unit metering are shown in drawings "MS-10A, MS-10B, MS-20A, MS-20B, MS-30B and MS-30C."
- 3.3.5 All new multi-tenant buildings shall be individually metered by WNHI or a licensed Sub-Metering provider.
- 3.3.6 For existing apartment buildings, the owner may choose to switch from bulk metering to WNHI individual



metering.

- 3.3.7 For row housing all meter bases for each block must be as per the design drawing. The owner is responsible for the extension of the unit services from the meter base to the individual units.
- 3.3.8 For shopping plaza and industrial mall metering, WNH or a licensed Sub-Metering provider shall individually meter each separate store, shop, or industrial unit located in a shopping plaza.

3.4 Three Phase Services

3.4.1 Services without switchgear:

For all three-phase services 225-800 amperes, without switchgear.

- a) Refer to drawings "MS-2, MS-30D, MS-30E, MS-30F and MS-30G" for equipment requirements and layout details.
- b) The Customer shall supply and install a 900mm x 900mm x 300mm (36" x 36" x 12") metering cabinet (stainless steel NEMA 3R if outdoors) and a WNH approved 13 jaw meter base in accordance with the applicable metering drawings listed in 3.4.1(a). See Appendix B for approved 13 Jaw meter bases.
- c) See drawing "MS-30H" for alternate 13 jaw meter locations.
- d) Additional notes for services requiring metering cabinets:
 - i. The Customer shall supply and install bonding as shown in drawing "MS-2".
 - ii. Bar type current transformers maybe used when the main switch is located more than 12" from the metering cabinet. When bar type CT's are used, the Customer's Electrician shall supply a neutral block and all necessary lugs for conductor terminations on both sides of the CT's. The Customer's Electrician shall install WNH supplied heat shrink to all exposed CT connections prior to energizing the service.
 - iii. The Customer or Contractor shall contact WNH's Metering Department to arrange a time for back plate drop-off during regular business hours. A minimum of 10 working days is required for WNH staff to build and install the metering equipment. Upon completion, WNH's Metering Department shall notify the Customer or Contractor and arrange a date and time (during normal working hours) to meet on site for delivery of the back plate. It is the Customer's or a Contractor's responsibility to install the back plate at time of delivery.
 - iv. Within 10 working days of meter back plate installation, the Customer shall supply and install a grounded 120VAC duplex receptacle fed from a dedicated 15A single-pole breaker and routed via EMT conduit. Wiring to receptacle to be kept to minimum length possible.
- e) Interval meters shall be installed for all new or upgraded services where the monthly average peak demand over a calendar year could exceed 50 kW or greater. Refer to Section 3.7.

3.4.2 Services with switchgear:

For three-phase services greater than or equal to 225 amperes with switchgear:

- a) Refer to drawings "MS-20B, MS-30A, MS-30B and MS-30C" for equipment requirements and layout details.



- b) The Customer shall provide WNHI at least 2 sets of original switchgear drawings from the manufacturer. Any discrepancies between the submitted drawings and the equipment on-site shall require re-submittal of new drawings. WNHI will not provide comment on 'as-built' switchgear drawings. Any deficiencies, caused as a result of not coordinating switchgear-drawing approval beforehand, must be remedied by the Contractor/Customer at their expense. All switchgear drawings are subject to review and approval by WNHI, and must include the following information:
 - i. Switchgear manufacturer contact information
 - ii. Project and job number
 - iii. Complete shipping address for the instrument transformers
 - iv. Full name and phone number(s) of the contact person(s)
 - v. The Customer shall supply and install a 13 Jaw meter base. For the current list of approved meter bases, refer to Appendix B.
- c) WNHI shall provide the necessary current and potential transformers and these can be either shipped to the switchgear manufacturer (with reasonable notice) or installed locally by the Customer/Contractor. WNHI shall not be responsible to install these transformers or perform any bus modifications.
- d) The Customer shall supply and install a grounded 120VAC duplex receptacle, fed from a dedicated 15A single-pole breaker, routed via EMT conduit and located within 12" from the meter base. Wiring to the receptacle is to be the minimum length possible.
- e) The Customer or Contractor shall contact WNHI Metering Department when conduit, IT's, meter base and 120VAC duplex receptacle have been installed. Allow a minimum of 10 working days for WNHI staff to build and install the metering equipment.
- f) Interval meters shall be installed for all new or upgraded services where the monthly average peak demand over a calendar year could exceed 50 kW or greater.

3.5 Central Metering

- 3.5.1 Central metering may be provided at the discretion of WNHI. This involves the installation of IT's at the transformer location to meter secondary cables running to typically two or more buildings on the same property, typically installed in rural areas.
- 3.5.2 For single-phase installations, refer to drawings "MS-10C or MS-10E".
 - a) The Customer shall supply and install a WNHI approved 5-jaw (5th jaw at 9 o'clock position) meter base with automatic bypass for the current circuit on the left side jaws. See Appendix B for approved meter bases.
- 3.5.3 For three phase installations, refer to drawings "MS-30E", "MS-30F" or "MS-30G".
 - a) The Customer shall supply and install a 900mm x 900mm x 300mm (46" x 46" x 12") NEMA 3R stainless steel metering cabinet and a WNHI approved 13 jaw meter base in accordance with the applicable metering drawings listed in 3.5.3. See Appendix B for approved meter bases.
 - b) Additional notes for services requiring metering cabinets:
 - i. The Customer shall supply and install bonding as shown in drawing "MS-2".



METERING SPECIFICATIONS

- ii. The Customer or Contractor shall contact WNHI's Metering Department to arrange a time for back plate drop-off during regular business hours. A minimum of 10 working days is required for WNHI staff to build and install the metering equipment. Upon completion, WNHI's Metering Department shall notify the Customer or Contractor and arrange a day and time (during normal working hours) to meet on site for delivery of the back plate. It is Customer's or a Contractor's responsibility to install the back plate at time of delivery.
 - iii. Within 10 working days of meter back plate installation, the Customer shall supply and install a grounded 120VAC duplex receptacle fed from a dedicated 15A single-pole breaker and routed via EMT conduit. Wiring to the receptacle is to be the minimum length possible.
- 3.5.4 For pole mounted CMS installations, all central metering equipment shall be located on the transformer pole unless an intermediate pole is required. The pole shall be a minimum 40' Class 3 Wood pole, supplied and installed by the Customer.
- 3.5.5 For pad mounted central metering the CT's shall be located inside the WNHI pad mount transformer. The meter and potential transformers (PT's) (if required) shall be located on 6"x6" pressure treated post(s) or a freestanding meter cabinet structure. See drawings listed in 3.5.2 and 3.5.3 for specific installation details.
- 3.5.6 The Customer shall supply and install a continuous 32mm (1") PVC conduit from the meter base/cabinet to the CT's.
- 3.5.7 Interval meters shall be installed for all new or upgraded services where the monthly average peak demand over a calendar year could exceed 50kW or greater.
- 3.6 Primary Metering**
 - 3.6.1 Primary metering may be a requirement of WNHI. A deposit payable in full to WNHI is required before WNHI orders such equipment. WNHI shall retain ownership of primary metering equipment.
 - 3.6.2 Each primary metered service shall be reviewed thoroughly and on an individual basis. The Customer and/or their agent shall submit to WNHI all required switchgear and electrical single line drawings in a timely manner to allow for WNHI's reviews and comments.
 - 3.6.3 Primary metering potential transformers in Customer-owned switchgear shall be installed in a manner that permits fuse and/or PT replacement while the service is energized via:
 - a) PT's and fuses mounted on a tilt-out drawer or slide-out tray, or
 - b) Fuses mounted on a slide-out tray with PT's in a separate compartment, allowing for all of the following positions:
 - i. connected
 - ii. isolated
 - iii. grounded
 - 3.6.4 Provisions for padlocking to be provided for the connected and grounded positions of the PT drawer/tray.
 - 3.6.5 The PT/fuse compartment(s) must be fully barriered from remaining compartments to permit servicing of PT or fuses while the remainder of switchboard is energized.
 - 3.6.6 All clearances shall be per the Electrical Safety Code. Any field modifications shall be subject to Electrical Safety Authority (ESA) Inspection and Canadian Standards Association (CSA) field evaluation.
 - 3.6.7 Contact WNHI early in the design stage to begin the review process as additional standards and requirements for primary metering may apply. Note that WNHI does not stock either Primary Metering Units (PMU's) or Primary Metering Transformers and that this equipment typically has long lead times.



3.7 Interval Metering

- 3.7.1 Interval meters shall be installed for all new or upgraded services where the monthly average peak demand over a calendar year could exceed 50 kW or greater. Some interval metering applications may require the installation of a third party communication line for reading the meter. Once approved by the Ontario Energy Board (OEB), the Customer shall pay to WNHI a Meter Communication Charge (or equivalent) for the communication line that is used to remotely read the customer's electric meter.
- 3.7.2 Metering applications that require a cellular or analogue communications include:
- i. Meters installed below grade with insufficient WNHI private network coverage.
 - ii. Legacy customers that have read only access through ITRON MV90 software.
 - iii. Metering installations that are registered with the IESO.

3.8 Generation Metering

This section defines the metering requirements for embedded generators connected to WNHI's distribution system. In particular, this section applies to the following types of generation:

- i. Net metering
 - ii. IESO contracted generators through micro FIT and FIT programs
 - iii. Load displacement generators
 - iv. Emergency backup generators
- 3.8.2 Each distributed generation service with the exception of Micro Generators (<10kW Capacity) shall be reviewed thoroughly and on an individual basis. The Customer and/or their agent shall submit to WNHI all required switchgear and electrical single line drawings in a timely manner to allow for WNHI's reviews and comments. The metering installation shall be installed in accordance with the Connection Impact Assessment, Connection Cost Agreement, Distribution Connection Agreement, and Conditions of Service.
- 3.8.3 The Customer shall contact WNHI Engineering early in the design stage to begin the review as additional requirements for distribution system upgrades, remote Supervisory Control and Data Acquisition (SCADA) monitoring and transfer trip may apply.

Net Metering

- 3.8.4 WNHI will install, at the Customers cost, a bi-directional meter at the service entrance to measure energy in the delivered and received directions.
- 3.8.5 Net Metered services that have a total capacity greater than 50kW shall supply a second bi-directional meter at the generator output. The generator meter will be used for power quality monitoring and a future capacity reserve charge (or equivalent) once approved by the Ontario Energy Board. Refer to drawing "MS-50A or MS-50B" for equipment requirements and layout details.

IESO Contracted Generators through Micro FIT and FIT Programs

- 3.8.6 WNHI offers two connection options for Micro FIT and FIT generators:



i. Direct Connection

In a direct connection, the embedded generator is directly connected to the WNHI distribution through a Customer owned transformer. The embedded generator meter and station service meter (if required) shall be installed on the secondary side of the Customer's transformer.

ii. Indirect Parallel Connection

In an indirect parallel connection, the embedded generator is connected to an existing load service and the metering for the embedded generator is independent of the load service meter.

- 3.8.7 The point of connection for an embedded generator shall be specified on the WNHI Offer To Connect. Typical locations are the line side of a three phase main disconnect switch or a single-phase multi-position meter base.
- 3.8.8 For three phase micro generators with a capacity less than 10kW the Customer shall supply a WNHI approved meter base. For the current list of approved meter bases, refer to Appendix B. Refer to drawing "MS-50A" for equipment requirements and layout details for three phase generators.
- 3.8.9 For embedded generators with a capacity greater than 10kW the Customer shall provide transformer type metering. Refer to drawing "MS-50B" for equipment requirements and layout details for three phase generators.

Load Displacement Generators:

- 3.8.10 Load displacement generators that have a total nameplate capacity greater than 50kW shall supply a second meter at the generator output. The generator meter will be used for power quality monitoring and a future capacity reserve charge (or equivalent) if approved by the Ontario Energy Board. Refer to drawing "MG-50A or MS-50B" for equipment requirements and layout details.
- 3.8.11 Load displacement generators greater than 1MW may be subject to Hydro One gross load billing charges and IESO meter registration. Projects above the 1MW threshold are reviewed on an individual basis and may be subject to additional standards and requirements.

Emergency Backup Generators

- 3.8.12 WNHI Customers are allowed to purchase portable emergency backup generators. These generators must be installed on the load side of the WNHI metering equipment.
- 3.8.13 For portable emergency backup generation, residential Customers can install a WNHI approved plug-in transfer device onto a 200A, 4-jaw meter base that is installed outdoors. Before installation of a plug-in transfer device Customers must contact WNHI's Engineering Department, sign an "Approved Meter-Base Transfer Device Waiver and Release Form", and receive an Offer to Connect Layout from the Engineering department authorizing the installation of the plug-in transfer device. See Appendix C for approved plug-in transfer devices.
- 3.8.14 Customers may install a combination meter base with service entrance rated breaker and automatic transfer switch. The combination meter must be installed outdoors and shall only be allowed for residential Customers with 120/240V, single phase services up to 200 Amps. See Appendix C for approved combination meter bases.

3.9 Pulse Outputs

- 3.9.1 Customers may request access to WNHI's real time meter data for supplying inputs to their energy management systems. For most three-phase services greater than 200 Amps, WNHI will provide



Customer access to certain KYZ metering pulse output(s) after completing a site review and quotation for the Customer.

- 3.9.2 The Customer shall be responsible for all costs associated with supplying access to the metering pulse outputs.
- 3.9.3 The "WNHI Metering Pulse Output(s) Access Agreement" must be completed and sent to WNHI for approval.

3.10 Fire Equipment Connection

- 3.10.1 If a separate service for a fire pump has been deemed necessary to comply with legislation, codes or regulations under emergency conditions involving a fire, WNHI will offer it subject to the following additional requirements:
 - i. A single line diagram showing the connection of the fire pump and meter base voltage and current ratings shall be submitted to WNHI.
 - ii. The main disconnect and meter base for the fire pump service shall be located in the same room as the main breaker for the overall service.
- 3.10.2 Laminated warning cards must be located at both the main disconnect for the fire pump service and at the main disconnect for the main secondary service (permanently affixed). They must be red with white lettering and the lettering must be a minimum of 12.7mm (0.5") in size. Wording on these cards must be "Fire Pump Installed Ahead of Main Breaker. Two (2) separate points of secondary supply exist in this room. There is a possibility of electrical back feed."



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

4. APPENDICIES



Appendix 'A'

Metering Standards

| Standard Number | Standard Title |
|-----------------|--|
| MS-1 | Multiple-Unit Metering Identification Detail |
| MS-2 | Bonding, Metering Cabinets, Electronic Metering – Equipment Layout |
| MS-3 | Current Transformer for 201-1200 Amp Services – Ritz DCCW |
| MS-4 | Current Transformer for 1201-4000 Amp Services – Ritz DCEW |
| MS-5 | Current Transformer for 201-1500 Amp, Pad Mount Central Metered Services – Ritz DCDW |
| MS-6 | Potential Transformer for 347/600V Services – Ritz ME-7 |
| MS-10A | Single To Multiple Unit Metering Up To And Including 200 Amps, 120/240V, Single And Ganged Meter Bases, Underground Service – Equipment Layout |
| MS-10B | Multiple Unit Metering, Up To And Including 200 Amps Per Metered Sub-Service, 120/240V, Ganged Meter Bases, Underground or Overhead Service – Load Side Wiring Configuration Specification |
| MS-10C | Central Metered Pad Mount, Single Phase, 200-600 Amp, 120/240V Service – Equipment Layout |
| MS-10D | 400 Amp, Single-Phase, 120/240V With Transformer-Rated Combination Meter Base – Overhead or Underground Service - Equipment Layout |
| MS-10E | Central Metered Service, 200Amp To 600 Amp, 120/240V – Pole Mounted Transformer |
| MS-10F | 400 Amp, Single-Phase, 120/240V With Meter Cabinet |
| MS-20A | Multiple Unit Metering, Below 225 Amps – 120/240V, 120/208V And 347/600V Without Meter Centre – Equipment Layout |
| MS-20B | Multiple Unit Metering, Up to 200A – 120/240V, 120/208V And 347/600V With Meter Centre – Equipment Layout |
| MS-30A | Meter Base – Standard Mounting Layout for Three Phase, Secondary Services With Low-Voltage Switchgear, 120/208V or 347/600V |
| MS-30B | Multiple Unit Metering, Combination of Services Below And Above 225 Amps – 120/240V, 120/208V And 347/600V – Equipment Layout |
| MS-30C | Multiple Unit Metering – Combination of Service Sizes With Transformer Discount Meter – 120/240V, 120/208V And 347/600V – Equipment Layout |
| MS-30D | Meter Cabinet – Standard Mounting Layout For Three Phase, Secondary Services 225-800 Amps Without Switchgear |



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

| Standard Number | Standard Title |
|-----------------|---|
| MS-30E | Central Metered Service, 128/208V And 347/600V, 225-800 Amps – Equipment Layout |
| MS-30F | Central Metered Pad Mount, Three Phase, 200-1200 Amp, 120/208V Service – Equipment Layout |
| MS-30G | Central Metered Pad Mount, Three Phase, 200-1200 Amp, 347/600V Service – Equipment Layout |
| MS-30H | Alternate Meter Locations For Buildings With A Three Phase Service And A Sub-Grade Electrical Room |
| MS-50A | Meter Base – Standard Mounting Layout For Three Phase, Distributed Generation Secondary Services, 120/208V or 347/600V Below 225A |
| MS-50B | Meter Cabinet – Standard Mounting Layout For Distributed Generation Secondary Services, 120/208V or 347/600V, 225-800 Amps Without Switchgear |



WATERLOO NORTH HYDRO INC.


DATE:
2021-03-23SCALE:
NTSREV.
1

DWG. NO.


MS-1

TITLE: MULTIPLE UNIT METERING IDENTIFICATION DETAIL


① DOOR TO UNIT



② UNIT MAIN SWITCH/BREAKER



③ UNIT METER BASE



- ① UNIT NUMBER MUST BE PERMANENTLY MARKED, EASILY IDENTIFIABLE AND A MINIMUM TEXT SIZE OF 50mm (2"). PERMANENT MARKER OR NUMBERS ON PAPER TAPED TO DOOR ARE NOT ACCEPTABLE MEANS OF UNIT IDENTIFICATION
- ② UNIT NUMBER MUST BE PERMANENTLY MARKED ON MAIN SWITCH/BREAKER. PERMANENT MARKER ACCEPTABLE ON INDOOR EQUIPMENT
- ③ UNIT NUMBER MUST BE PERMANENTLY MARKED ON NON-REMOVABLE PORTION OF METER BASE (AS SHOWN) AND ALSO MARKED ON THE INSIDE OF THE METER BASE. ACCEPTABLE MEANS OF MARKING INCLUDE ENGRAVED WITH ELECTRIC ETCHER, CENTER PUNCH DOTS (AS SHOWN), PAINT OR PERMANENT MARKER. PERMANENT MARKER ONLY ACCEPTABLE ON INDOOR EQUIPMENT
- ④ STREET ADDRESS FOR BUILDING MUST BE CLEARLY POSTED
- ⑤ UNITS NOT SUFFICIENTLY IDENTIFIED WILL NOT BE CONNECTED UNTIL IN COMPLIANCE WITH THIS STANDARD



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
DateD. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2020-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-2


TITLE: **BONDING, METERING CABINETS, ELECTRONIC METERING
EQUIPMENT LAYOUT**



- ① #6 CU (GREEN INSULATION) TO MAIN SERVICE GROUND SUPPLIED AND INSTALLED BY CUSTOMER/CONTRACTOR
- ② 150mm TO 200mm (6" TO 8") AFTER ENTERING CABINET, TERMINATE AT BONDING LUG AND CONTINUE TAIL TO LOWER RIGHT CORNER OF BACK PLATE
- ③ #12 CU (GREEN INSULATION) TO HYDRO METERING EQUIPMENT AND BOND CONNECTOR
- ④ METERING CABINET TO BE COMPLETE WITH A REMOVABLE BACK PLATE & TWO (2) SIDE HINGED OPENING DOORS

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC **MAY 1, 2021**
Date

D. Moryc, P. Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-3

TITLE: CURRENT TRANSFORMER FOR 201 - 1200 AMP SERVICES
RITZ DCCW



GENERAL NOTES:

- SEE RITZUSA.COM FOR DETAILED SPECIFICATIONS FROM MANUFACTURER

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |

Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

Dorothy Moryc May 1, 2021
Date

D. Moryc, P. Eng.
Signature & Professional Designation





WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-5

TITLE: CURRENT TRANSFORMER FOR 201 - 1500 AMP, PAD MOUNT CENTRAL METERED
SERVICES - RITZ DCDW



GENERAL NOTES:

- SEE RITZUSA.COM FOR DETAILED SPECIFICATIONS FROM MANUFACTURER

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |

Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc
Signature & Professional Designation





WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23






SCALE:
NTS

REV.
1

DWG. NO.

MS-6

TITLE: **POTENTIAL TRANSFORMER FOR 347/600V SERVICES**
RITZ ME-7



GENERAL NOTES:

- SEE RITZUSA.COM FOR DETAILED SPECIFICATIONS FROM MANUFACTURER

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |

Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc, P. Eng
Signature & Professional Designation





WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-10A


TITLE: SINGLE TO MULTIPLE UNIT METERING UP TO AND INCLUDING 200A, 120/240V, SINGLE AND GANGED METER BASES, OVERHEAD OR UNDERGROUND SERVICE - EQUIPMENT LAYOUT



- ① METER BASE(S) TO BE LOCATED ON EXTERIOR OF BUILDING AND MOUNTED AT 1.6m(5'4") \pm 100mm(4") FROM FINISHED ELEVATION TO CENTER OF METER GLASS/FACE. SEE SELECTION TABLE IN APPENDIX B FOR APPROVED METER BASES
- ② METER BASE(S) TO BE WITHIN 3m OF FRONT CORNER OF BUILDING
- ③ ALL MULTI-POSITION METER BASES MUST HAVE A BLANK CONNECTION COMPARTMENT
- ④ METERING SPECIFICATIONS MS-1 AND MS-10D APPLY FOR MULTI-UNIT METERING INSTALLATIONS
- ⑤ CABLE AND CONDUIT LOCATIONS FOR LINE/LOAD CONDUCTORS MAY VARY DEPENDING ON OVERHEAD OR UNDERGROUND FEED CONFIGURATION

GENERAL NOTES:

- SEE APPENDIX A SELECTION TABLE FOR WNH APPROVED METER BASES
- WNH APPROVED METER BASE TO BE MOUNTED AND SECURED TO WALL AS PER ELECTRICAL SAFETY AUTHORITY (ESA) REQUIREMENTS
- NO PART OF METER BASE(S) IS PERMITTED TO BE ABOVE CENTRAL AIR CONDITIONERS, WINDOW WELLS OR ANY OBSTACLES THAT PREVENT ACCESS TO METER
- NO PART OF METER BASE IS PERMITTED WITHIN 1m OF GAS METER
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY Moryc *May 1, 2021*
Date

D. Moryc, P. Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-10B

TITLE: MULTIPLE UNIT METERING, UP TO AND INCLUDING 200 AMPS PER METERED SUB-SERVICE, 120/240V, GANGED METER BASES, UNDERGROUND OR OVERHEAD - LOAD SIDE WIRING CONFIGURATION SPECIFICATION



- ① UNIT NUMBERING ON METER BASE AS PER SPECIFICATION DRAWING MS-1
- ② LOAD SIDE OF HYDRO METER
- ③ BLANK COMPARTMENT IN METER BASE REQUIRED FOR ALL MULTI-POSITION METER BASES
- ④ CABLE AND CONDUIT LOCATIONS FOR LINE/LOAD CONDUCTORS MAY VARY DEPENDING ON OVERHEAD OR UNDERGROUND FEED CONFIGURATION

GENERAL NOTES:

- METER BASES TO NOT BE USED AS RACE WAY
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |




WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23SCALE:
NTSREV.
1

DWG. NO.


MS-10C

TITLE: CENTRAL METERED PAD MOUNT, SINGLE PHASE, 200-600 AMP, 120/240V
SERVICE - EQUIPMENT LAYOUT

- ① CUSTOMER/CONTRACTOR TO SUPPLY & INSTALL A WNH APPROVED 5-JAW METER BASE (5TH JAW IN THE 9 O'CLOCK POSITION) WITH AUTOMATIC BYPASS AT THE CURRENT CIRCUIT ON THE LEFT SIDE. METER BASE TO BE MOUNTED AT $1.6\text{m}(5'4") \pm 100\text{mm}(4")$ FROM FINISHED GRADE ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ② FREE STANDING STRUCTURE SPECIFICATIONS:
 - a. 1 - 6"x6"x10' PRESSURE TREATED POST (MINIMUM 1.22m (4')) INSTALLED SUB-GRADE
 - b. POSTS TO BE CONCRETE ENCASED IN MINIMUM 1.22m (4') DEEP SONOTUBES
 - c. POST TO BE LOCATED WITHIN 1m OF TRANSFORMER VAULT (INSIDE TRANSFORMER GROUNDING LOOP)
- ③ 25mm (1") PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT—MUST BE CONTINUOUS FROM PAD MOUNT TRANSFORMER TO METER BASE
- ④ HYDRO WILL SUPPLY AND INSTALL METERING C.T.'S AND METERING WIRE

GENERAL NOTES:

- SEE WNH UNDERGROUND STANDARDS DOCUMENT FOR TRANSFORMER AND CABLE INSTALLATION DETAILS
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)

**Certificate of Approval**

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
DateD. Moryc, P. Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1


DWG. NO.

MS-10D

TITLE: 400 AMP, SINGLE-PHASE, 120/240V WITH TRANSFORMER-RATED COMBINATION
METER BASE - OVERHEAD OR UNDERGROUND SERVICE - EQUIPMENT LAYOUT




FREE STANDING STRUCTURE
CONSTRUCTION DETAIL:
SEE NOTE 1 FOR REQUIREMENTS



- ① FREE STANDING STRUCTURE SPECIFICATIONS:
 - a. 2 - 6"X6"X10' PRESSURE TREATED POSTS (MINIMUM 1.22m (4')) INSTALLED SUB-GRADE
 - b. POSTS TO BE CONCRETE ENCASED IN MINIMUM 1.22m (4') DEEP SONOTUBES
 - c. BACKBOARD TO BE 16mm (5/8") OR 19mm (3/4") PLYWOOD WITH 25.4mm (1") OVERLAP ON ALL SIDES OF METER ENCLOSURE
- ② METER BASE DIMENSIONS (APPROXIMATE) 750mm X 460mm X 200mm (30" X 18" X 8") TO BE MOUNTED AT 1.6m(5'4") \pm 100mm(4") FROM FINISHED GRADE ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ③ WNH TO PROVIDE CURRENT TRANSFORMER (C.T.) AND WIRING ON SECONDARY SIDE OF C.T.
- ④ CUSTOMER/CONTRACTOR TO SUPPLY AND INSTALL ALL LUGS FOR CONNECTIONS ON PRIMARY SIDE OF C.T.
- ⑤ CABLE CONDUIT LOCATIONS FOR LINE/LOAD CONDUCTORS MAY VARY DEPENDING ON OVERHEAD OR UNDERGROUND FEED CONFIGURATION
- ⑥ 5-JAW METER BASE MUST BE EQUIPPED WITH AN AUTOMATIC BYPASS SWITCH FOR THE CURRENT CIRCUIT WITH 5TH JAW IN 9 O'CLOCK POSITION

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc, P. Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-10E

TITLE: **CENTRAL METERED SERVICE, 200 AMP TO 600 AMP, 120/240V - EQUIPMENT LAYOUT**



- ① CUSTOMER-OWNED TRANSFORMER POLE MUST BE:
 - a. SUPPLIED & INSTALLED BY CUSTOMER/CONTRACTOR (LOCATION SUBJECT TO HYDRO APPROVAL)
 - b. MINIMUM 40' CLASS 4 WOOD, PRESSURE-TREATED BUTT (TREATED WITH AN APPROVED WOOD PRESERVATIVE) TO APPROXIMATELY 300mm (12") ABOVE GRADE. MINIMUM SETTING DEPTH OF POLE: 1.8m (6').
 - c. BACK-GUYED & ANCHORED AS PER ESA (1.37m (54") FIBERGLASS ROD SHALL BE USED ON ALL GUYS)
 - d. FRAMED & INSULATED FOR 27.6KV OPERATING VOLTAGE
- ② METER BASE MOUNTING HEIGHT MUST BE 1.6m (5'4") \pm 100mm (4") FROM FINISHED GRADE TO CENTER OF METER FACE/GLASS
- ③ CUSTOMER/CONTRACTOR TO SUPPLY & INSTALL AN APPROVED 5-JAW METER BASE (5TH JAW IN THE 9 O'CLOCK POSITION) WITH AUTOMATIC BYPASS AT THE CURRENT CIRCUIT ON THE LEFT SIDE AND A 25mm (1") PVC CONDUIT UP THE POLE, COMPLETE WITH WEATHER HEAD AT SPECIFIED HEIGHT. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ④ HYDRO WILL SUPPLY & INSTALL THE METERING CT AND METERING WIRE
- ⑤ #6 BOND WIRE TO BE INSTALLED BY CUSTOMER/CONTRACTOR

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc, P. Eng
Signature & Professional Designation




WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23SCALE:
NTSREV.
1

DWG. NO.

MS-10F

TITLE: METER CABINET - STANDARD MOUNTING LAYOUT FOR SINGLE PHASE,
SECONDARY SERVICES 225-600 AMPS WITHOUT SWITCHGEAR

FINISHED FLOOR ELEVATION

- ① CUSTOMER/CONTRACTOR TO SUPPLY & INSTALL AN APPROVED 5-JAW METER BASE (5TH JAW IN THE 9 O'CLOCK POSITION) WITH AUTOMATIC BYPASS AT THE CURRENT CIRCUIT ON THE LEFT SIDE. METER BASE TO BE MOUNTED AT $1.6\text{m}(5'4") \pm 100\text{mm}(4")$ FROM FINISHED GRADE ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ② GROUNDED 120VAC DUPLEX RECEPTACLE - FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ③ METER CABINET DIMENSIONS $900\text{mm} \times 900\text{mm} \times 300\text{mm}$ ($36" \times 36" \times 12"$) OR ALTERNATE SIZE OF $1200\text{mm} \times 1200\text{mm} \times 300\text{mm}$ ($48" \times 48" \times 12"$) COMPLETE WITH REMOVABLE BACK PLATE AND 2 SIDE-HINGED CENTER OPENING DOORS. CABINET TO BE MOUNTED AT A HEIGHT OF $1.83\text{m}(6') \pm 50\text{mm}(2")$ FROM FINISHED FLOOR ELEVATION TO TOP OF CABINET
- ④ METER CABINET MUST BE SECURELY FASTENED TO SUPPORTING WALL WITH AN ADEQUATE NUMBER OF PROPERLY SIZED FASTENERS TO SUPPORT A FULLY LOADED CABINET AND BACK PLATE ASSEMBLY WEIGHT OF 90KG (200LBS)
- ⑤ FUSING REQUIRED ON POTENTIAL CONDUCTORS IF CONDUCTOR LENGTH IS $>3\text{m}$
- ⑥ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT-MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE
- ⑦ BONDING LUG AS PER DRAWING MS-2

GENERAL NOTES:

- ALL METERING CT'S & PT'S TO BE LOCATED ON LOAD SIDE OF MAIN DISCONNECT
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)

**Certificate of Approval**

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
DateD. Moryc, P. Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |




WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23SCALE:
NTSREV.
1

DWG. NO.


MS-20A

TITLE: MULTIPLE UNIT METERING, BELOW 225 AMPS - 120/240V, 120/208V AND 347/600V
WITHOUT METER CENTRE - EQUIPMENT LAYOUT

- ① APPROVED SUB-SERVICE METER BASE(S) WITH ISOLATED NEUTRAL BLOCK. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT $1.63\text{m}(5'4") \pm 50\text{mm}(2")$ FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ② METER BASE REQUIREMENTS FOR SINGLE PHASE SERVICES (1PH 3W):
 - a. 4-JAW METER BASE REQUIRED
 - b. LINE SIDE CONDUCTORS MUST BE ENERGIZED PRIOR TO METER INSTALLATION
 - c. NEUTRAL CONDUCTOR MUST BE BROUGHT INTO AND TERMINATED IN EACH METER BASE
- ③ METER BASE REQUIREMENTS FOR THREE PHASE SERVICES (3PH 4W):
 - a. 7-JAW METER BASE REQUIRED
 - b. ALL THREE PHASES TO THE LINE SIDE OF THE METER BASE MUST BE ENERGIZED PRIOR TO METER INSTALLATION
 - c. NEUTRAL CONDUCTOR MUST BE BROUGHT INTO AND TERMINATED IN EACH METER BASE
- ④ METER BASE REQUIREMENTS FOR NETWORK SERVICES (2PH 3W):
 - a. 5-JAW METER BASE REQUIRED WITH 5TH JAW IN 9 O'CLOCK POSITION
 - b. BOTH PHASES TO THE LINE SIDE OF THE METER BASE MUST BE ENERGIZED PRIOR TO METER INSTALLATION
 - c. NEUTRAL CONDUCTOR MUST BE BROUGHT INTO AND TERMINATED IN EACH METER BASE
- ⑤ EACH SUB-SERVICE IS TO BE COMPLETE WITH LOCKABLE DISCONNECT
- ⑥ UNIT LABELING AS PER METERING SPECIFICATION MS-1

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)

**Certificate of Approval**

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
DateD. Moryc, P.Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-20B


TITLE: **MULTIPLE UNIT METERING, UP TO 200A - 120/240V, 120/208V AND 347/600V WITH
METER CENTRE - EQUIPMENT LAYOUT**



- ① UNIT NUMBERING AS PER DRAWINGS MS-1
- ② EACH SUB-DISCONNECT SWITCH TO BE COMPLETE WITH LOCKABLE DISCONNECT
- ③ MINIMUM MOUNTING HEIGHT OF BOTTOM METER: 0.6m (24") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER FACE
- ④ MAXIMUM MOUNTING HEIGHT OF TOP METER: 1.6m (5'4") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER FACE
- ⑤ ALL ELECTRICAL INPUTS TO THIS EQUIPMENT MUST BE CONNECTED ON THE LOAD SIDE OF THE REVENUE METERING INSTRUMENTS, OUTSIDE OF THE METERING TRANSFORMER COMPARTMENT

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
Date

D. Moryc, P. Eng
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-30A

TITLE: METER BASE - STANDARD MOUNTING LAYOUT FOR THREE PHASE, SECONDARY SERVICES WITH LOW-VOLTAGE SWITCHGEAR, 120/208V OR 347/600V




FINISHED FLOOR ELEVATION

- ① 13-JAW METER BASE. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m(5'4") \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES AND METERING SPECIFICATION MS-30H FOR ALTERNATE METER LOCATIONS
- ② GROUNDED 120VAC DUPLEX RECEPTACLE – FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ③ ALL ELECTRICAL INPUTS TO THIS EQUIPMENT MUST BE CONNECTED ON THE LOAD SIDE OF THE REVENUE METERING INSTRUMENTS, OUTSIDE OF THE METERING TRANSFORMER COMPARTMENT
- ④ FUSING REQUIRED ON POTENTIAL CONDUCTORS IF CONDUCTOR LENGTH IS $>3m$
- ⑤ REVENUE METERING INSTRUMENT TRANSFORMER COMPARTMENT
- ⑥ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT—MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE
- ⑦ PHASE MARKING TAPE – RED, YELLOW, BLUE (LEFT TO RIGHT)

GENERAL NOTES:

- ALL METERING CT'S & PT'S TO BE LOCATED ON LOAD SIDE OF MAIN DISCONNECT
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
Date

D. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |




WATERLOO NORTH HYDRO INC.

DATE:
2021-03-26SCALE:
NTSREV.
1

DWG. NO.

MS-30B

TITLE: **MULTIPLE UNIT METERING, COMBINATION OF SERVICES BELOW AND ABOVE
225 AMPS - 120/240V, 120/208V AND 347/600V - EQUIPMENT LAYOUT**

- ① 13-JAW METER BASE. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m(5'4") \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES AND METERING SPECIFICATION MS-30H FOR ALTERNATE METER LOCATIONS
- ② SUB-SERVICE METER BASES:
 - a. 4-JAW FOR SINGLE PHASE SERVICES (1PH 3W)
 - b. 7-JAW FOR THREE PHASE SERVICES (3PH 4W)
 - c. 5-JAW FOR NETWORK SERVICES (2PH 3W). 5TH JAW IN 9 O'CLOCK POSITION
SEE WNH METERING SPECIFICATION MS-20A FOR FURTHER SUB-SERVICE REQUIREMENTS AND APPENDIX A SELECTION TABLE FOR APPROVED METER BASES
- ③ GROUNDED 120VAC DUPLEX RECEPTACLE - FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ④ ALL ELECTRICAL INPUTS TO THIS EQUIPMENT MUST BE CONNECTED ON THE LOAD SIDE OF THE REVENUE METERING INSTRUMENTS, OUTSIDE OF THE METERING TRANSFORMER COMPARTMENT
- ⑤ FUSING REQUIRED ON POTENTIAL CONDUCTORS IF CONDUCTOR LENGTH IS >3m
- ⑥ REVENUE METERING INSTRUMENT TRANSFORMER COMPARTMENT
- ⑦ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT-MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE
- ⑧ PHASE MARKING TAPE - RED, YELLOW, BLUE (LEFT TO RIGHT)
- ⑨ EACH SUB-SERVICE IS TO BE COMPLETE WITH LOCKABLE DISCONNECT
- ⑩ UNIT LABELING AS PER METERING SPECIFICATION MS-1

GENERAL NOTES:

- ALL METERING CT'S & PT'S TO BE LOCATED ON LOAD SIDE OF MAIN DISCONNECT
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)

**Certificate of Approval**

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
DateD. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/26/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-30C


TITLE: **MULTIPLE UNIT METERING, COMBINATION OF SERVICE SIZES WITH TRANSFORMER DISCOUNT METER - 120/240V, 120/208V AND 347/600V - EQUIPMENT LAYOUT**



- ① 13-JAW METER BASE. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m(5'4") \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES AND METERING SPECIFICATION MS-30H FOR ALTERNATE METER LOCATIONS
- ② GROUNDED 120VAC DUPLEX RECEPTACLE – FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ③ MINIMUM MOUNTING HEIGHT OF BOTTOM METER: 0.6m (24") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER FACE
- ④ MAXIMUM MOUNTING HEIGHT OF TOP METER: 1.6m (5'4") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER FACE
- ⑤ ALL ELECTRICAL INPUTS TO THIS EQUIPMENT MUST BE CONNECTED ON THE LOAD SIDE OF THE REVENUE METERING INSTRUMENTS, OUTSIDE OF THE METERING TRANSFORMER COMPARTMENT
- ⑥ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT—MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE
- ⑦ SECONDARY TRANSFORMER DISCOUNT METERING COMPARTMENT (IF APPLICABLE)
- ⑧ REVENUE METERING INSTRUMENT TRANSFORMER COMPARTMENT
- ⑨ PHASE MARKING TAPE – RED, YELLOW, BLUE (LEFT TO RIGHT)
- ⑩ UNIT NUMBERING AS PER DRAWINGS MS-1
- ⑪ FUSING REQUIRED ON POTENTIAL CONDUCTORS IF CONDUCTOR LENGTH IS >3m
- ⑫ SUB-SERVICE METER BASES:
 - a. 4-JAW FOR SINGLE PHASE SERVICES (1PH 3W)
 - b. 7-JAW FOR THREE PHASE SERVICES (3PH 4W)
 - c. 5-JAW FOR NETWORK SERVICES (2PH 3W). 5TH JAW IN 9 O'CLOCK POSITION
 ALL PHASES TO THE LINE SIDE OF THE METER BASE MUST BE ENERGIZED PRIOR TO METER INSTALLATION. NEUTRAL CONDUCTOR MUST BE BROUGHT INTO AND TERMINATED IN EACH METER BASE

GENERAL NOTES:

- ALL METERING CT'S & PT'S TO BE LOCATED ON LOAD SIDE OF MAIN DISCONNECT
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
Date

D. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-30D

TITLE: METER CABINET - STANDARD MOUNTING LAYOUT FOR THREE PHASE,
SECONDARY SERVICES 225-800 AMPS WITHOUT SWITCHGEAR




FINISHED FLOOR ELEVATION

- ① 13-JAW METER BASE. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m (5'4") \pm 50mm (2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES AND METERING SPECIFICATION MS-30H FOR ALTERNATE METER LOCATIONS
- ② GROUNDED 120VAC DUPLEX RECEPTACLE - FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ③ METER CABINET DIMENSIONS 900mm x 900mm x 300mm (36"x36"x12") OR ALTERNATE SIZE OF 1200mm X 1200mm X 300mm (48"x48"x12") COMPLETE WITH REMOVABLE BACK PLATE AND 2 SIDE-HINGED CENTER OPENING DOORS. CABINET TO BE MOUNTED AT A HEIGHT OF 1.83m(6') \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO TOP OF CABINET
- ④ METER CABINET MUST BE SECURELY FASTENED TO SUPPORTING WALL WITH AN ADEQUATE NUMBER OF PROPERLY SIZED FASTENERS TO SUPPORT A FULLY LOADED CABINET AND BACK PLATE ASSEMBLY WEIGHT OF 90KG (200LBS)
- ⑤ FUSING REQUIRED ON POTENTIAL CONDUCTORS IF CONDUCTOR LENGTH IS >3m
- ⑥ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT-MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE
- ⑦ PHASE MARKING TAPE - RED, YELLOW, BLUE, WHITE (TOP TO BOTTOM)
- ⑧ BONDING LUG AS PER DRAWING MS-2

GENERAL NOTES:

- ALL METERING CT'S & PT'S TO BE LOCATED ON LOAD SIDE OF MAIN DISCONNECT
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

Dorothy Moryc *May 1, 2021*
Date

D. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |




WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23SCALE:
NTSREV.
1

DWG. NO.

MS-30E


TITLE: CENTRAL-METERED SERVICE, 120/208V AND 347/600V, 225 - 800 AMPS -
EQUIPMENT LAYOUT

ALTERNATE METER CABINET
INSTALLATION:
FREE STANDING STRUCTURE
CONSTRUCTION DETAIL
SEE NOTE 1 FOR REQUIREMENTS

- ① FREE STANDING STRUCTURE SPECIFICATIONS:
 - a. 2 - 6"x6"x10' PRESSURE TREATED POSTS (MINIMUM 1.22m (4')) INSTALLED SUB-GRADE
 - b. POSTS TO BE CONCRETE ENCASED IN MINIMUM 1.22m (4') DEEP SONOTUBES
 - c. BACKBOARD TO BE 16mm (5/8") OR 19mm (3/4") PLYWOOD WITH 25.4mm (1") OVERLAP ON ALL SIDES OF METER ENCLOSURE
- ② HYDRO WILL SUPPLY AND INSTALL TRANSFORMER RACK, C.T.'S AND METERING WIRING
- ③ CUSTOMER TO SUPPLY AND INSTALL MINIMUM 45' CLASS 3 WOOD POLE
- ④ 900mm X 900mm X 300mm (36"x36"x12") STAINLESS STEEL METERING CABINET MOUNTED AT 1.83m ±50mm (6'±2") FROM FINISHED GRADE ELEVATION TO TOP OF THE CABINET
- ⑤ ALL CONDUITS ENTERING CABINET TO ENTER CABINET FROM BOTTOM ONLY
- ⑥ FUSING REQUIRED IF POTENTIAL CONDUCTORS ARE >3m
- ⑦ METER CABINET MUST BE SECURELY FASTENED TO POLE WITH AN ADEQUATE NUMBER OF PROPERLY SIZED FASTENERS TO SUPPORT A FULLY LOADED CABINET AND BACK PLATE ASSEMBLY WEIGHT OF 114KG (250LBS) COMPLETE WITH SIDE BRACING
- ⑧ GROUNDED 120VAC DUPLEX RECEPTACLE FED FROM DEDICATED 15A SINGLE POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER/CONTRACTOR AND ROUTED VIA EMT CONDUIT
- ⑨ CONDENSATION HEATER COMPLETE WITH 120V PLUG END
- ⑩ BONDING LUG AS PER METERING SPECIFICATION MS-2
- ⑪ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50'). MUST BE CONTINUOUS FROM WEATHER HEAD TO METER CABINET

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)

**Certificate of Approval**

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
Date

D. Moryc P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.


DATE:
2021-03-23SCALE:
NTSREV.
1

DWG. NO.

MS-30F


TITLE: CENTRAL METERED PAD MOUNT, THREE PHASE, 200-1200 AMP, 120/208V
SERVICE - EQUIPMENT LAYOUT

FRONT VIEW



FINISHED GRADE

SIDE VIEW



- ① 13-JAW METER BASE. METER BASE TO BE MOUNTED AT 1.63m (5'4") \pm 50mm (2") FROM FINISHED GRADE TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ② 25mm (1") EMT OR PVC SLEEVE FROM PAD MOUNT TRANSFORMER TO 13-JAW METER BASE
- ③ CURRENT TRANSFORMERS AND METERING WIRE TO BE SUPPLIED AND INSTALLED BY METERING DEPARTMENT
- ④ PHASE MARKING TAPE - RED (X1), YELLOW (X2), BLUE (X3), WHITE (X0)

GENERAL NOTES:

- SEE WNH UNDERGROUND STANDARDS DOCUMENT FOR TRANSFORMER AND CABLE INSTALLATION DETAILS
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE

**Certificate of Approval**

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
DateD. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-30G


TITLE: CENTRAL METERED PAD MOUNT, THREE PHASE, 200-1200 AMP, 347/600V
SERVICE - EQUIPMENT LAYOUT



- ① FREE STANDING STRUCTURE SPECIFICATIONS:
 - a. 2 - 6"x6"x10' PRESSURE TREATED POSTS (MINIMUM 1.22m (4')) INSTALLED SUB-GRADE
 - b. POSTS TO BE CONCRETE ENCASED IN MINIMUM 1.22m (4') DEEP SONOTUBES
 - c. BACKBOARD TO BE 16mm (5/8") OR 19mm (3/4") PLYWOOD WITH 25.4mm (1") OVERLAP ON ALL SIDES OF METER ENCLOSURE
- ② HYDRO WILL SUPPLY AND INSTALL C.T.'S, P.T.'S AND METERING WIRING
- ③ 900mm X 900mm X 300mm (36"x36"x12") STAINLESS STEEL METERING CABINET MOUNTED AT 1.83m \pm 50mm (6' \pm 2") FROM FINISHED GRADE ELEVATION TO TOP OF THE CABINET
- ④ ALL CONDUITS ENTERING CABINET TO ENTER CABINET FROM BOTTOM ONLY
- ⑤ FUSING REQUIRED IF POTENTIAL CONDUCTORS ARE >3m
- ⑥ METER CABINET MUST BE SECURELY FASTENED TO POSTS WITH AN ADEQUATE NUMBER OF PROPERLY SIZED FASTENERS TO SUPPORT A FULLY LOADED CABINET AND BACK PLATE ASSEMBLY WEIGHT OF 114KG (250LBS) COMPLETE WITH SIDE BRACING
- ⑦ GROUNDED 120VAC DUPLEX RECEPTACLE FED FROM DEDICATED 15A SINGLE POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER/CONTRACTOR AND ROUTED VIA EMT CONDUIT
- ⑧ CONDENSATION HEATER COMPLETE WITH 120V PLUG END
- ⑨ BONDING LUG AS PER METERING SPECIFICATION MS-2
- ⑩ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50'). MUST BE CONTINUOUS FROM WEATHER HEAD TO METER CABINET
- ⑪ PHASE MARKING TAPE - RED (X1), YELLOW (X2), BLUE (X3), WHITE (X0)

GENERAL NOTES:

- SEE WNH UNDERGROUND STANDARDS DOCUMENT FOR TRANSFORMER AND CABLE INSTALLATION DETAILS
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-30H

TITLE: ALTERNATE METER BASE LOCATIONS FOR BUILDINGS WITH A THREE PHASE SERVICE AND A SUB-GRADE ELECTRICAL ROOM



SUB-GRADE MAIN ELECTRICAL SWITCH GEAR
CONTAINING METERING INSTRUMENTATION CELL

- ① 13-JAW METER BASE. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m(5'4") \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ② GROUNDED 120VAC DUPLEX RECEPTACLE – FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ③ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT – MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE

| REV. | DESCRIPTION | DATE | INITIALS |
|------|------------------|------------|----------|
| 1 | STANDARD CREATED | 03/23/2021 | BD |
| | | | |
| | | | |



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
Date

D. Moryc P. Eng.
Signature & Professional Designation



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-50A

TITLE: METER BASE - STANDARD MOUNTING LAYOUT FOR THREE PHASE, DISTRIBUTED
GENERATION SECONDARY SERVICES 120/208V OR 347/600V BELOW 225A




- ① CUSTOMER/CONTRACTOR TO SUPPLY AND INSTALL WNH APPROVED 7-JAW METER BASE COMPLETE WITH ISOLATED NEUTRAL BLOCK. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m(5'4") \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES
- ② NEUTRAL CONDUCTOR MUST BE BROUGHT INTO AND TERMINATED IN THE METER BASE
- ③ DG SOURCE AND DG SYSTEM DISCONNECT SWITCHES MUST BE LOCATED INSIDE THE SAME ELECTRICAL ROOM AND VISABLE FROM THE GENERATOR METER
- ④ EACH DISCONNECT IS TO BE LOCKABLE

GENERAL NOTES:

- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC May 1, 2021
Date

D. Moryc, P. Eng.
Signature & Professional Designation



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-23


SCALE:
NTS

REV.
1

DWG. NO.

MS-50B

TITLE: METER CABINET - STANDARD MOUNTING LAYOUT FOR DISTRIBUTED GENERATION
SECONDARY SERVICES, 120/208V OR 347/600V, 225-800 AMPS WITHOUT SWITCH GEAR



- ① 13-JAW METER BASE. METER BASE TO BE LOCATED ON GROUND LEVEL FLOOR AND MOUNTED AT 1.63m (5'4") \pm 50mm (2") FROM FINISHED FLOOR ELEVATION TO CENTER OF METER. SEE APPENDIX B SELECTION TABLE FOR APPROVED METER BASES AND METERING SPECIFICATION MS-30H FOR ALTERNATE METER LOCATIONS
- ② 50mm (2") EMT OR PVC SCADA RADIO CONDUIT (IF REQUIRED)—MUST BE CONTINUOUS FROM METERING CABINET TO BUILDING ROOF. REFER WNH ENGINEERING GENERATION CONTRACTS FOR FURTHER DETAILS.
- ③ GROUNDED 120VAC DUPLEX RECEPTACLE — FED FROM DEDICATED 15A SINGLE-POLE BREAKER, SUPPLIED & INSTALLED BY CUSTOMER'S CONTRACTOR
- ④ METER CABINET DIMENSIONS 1200mm X 1200mm X 300mm (48"x48"x12") COMPLETE WITH REMOVABLE BACK PLATE AND 2 SIDE-HINGED CENTER OPENING DOORS. CABINET TO BE MOUNTED AT A HEIGHT OF 1.83m(6') \pm 50mm(2") FROM FINISHED FLOOR ELEVATION TO TOP OF CABINET. STAINLESS STEEL NEMA 3R CABINET REQUIRED FOR OUTDOOR INSTALLATIONS
- ⑤ METER CABINET MUST BE SECURELY FASTENED TO SUPPORTING WALL WITH AN ADEQUATE NUMBER OF PROPERLY SIZED FASTENERS TO SUPPORT A FULLY LOADED CABINET AND BACK PLATE ASSEMBLY WEIGHT OF 90KG (200LBS)
- ⑥ FUSING REQUIRED ON POTENTIAL CONDUCTORS IF CONDUCTOR LENGTH IS $>3m$
- ⑦ 25mm (1") EMT OR PVC CONDUIT MAXIMUM LENGTH 15m (50') OF CONDUIT—MUST BE CONTINUOUS FROM FRONT OF SWITCHGEAR INSTRUMENT TRANSFORMER COMPARTMENT TO METER BASE
- ⑧ PHASE MARKING TAPE — RED, YELLOW, BLUE, WHITE (TOP TO BOTTOM)
- ⑨ BONDING LUG AS PER DRAWING MS-2
- ⑩ PT'S ONLY REQUIRED FOR 347/600V SERVICES

GENERAL NOTES:

- DG SOURCE AND DG SYSTEM DISCONNECT SWITCHES MUST LOCKABLE ARE TO BE LOCATED INSIDE THE SAME ELECTRICAL ROOM AND VISIBLE FROM THE GENERATOR METER
- ALL METERING CT'S & PT'S TO BE LOCATED ON LOAD SIDE OF DG SYSTEM DISCONNECT
- MAINTAIN A MINIMUM 1m (39") CLEARANCE IN FRONT OF METER BASE(S) AND INSTRUMENT TRANSFORMER COMPARTMENT(S)



Certificate of Approval

The installation work covered by this document meets the safety requirements of Section 4 of Regulation 22/04

DOROTHY MORYC *May 1, 2021*
Date

D. Moryc, P. Eng.
Signature & Professional Designation

| REV. | DESCRIPTION | DATE | INITIALS |
|------|----------------------------------|------------|----------|
| 1 | UPDATED TO NEW DRAFTING STANDARD | 03/23/2021 | BD |
| | | | |
| | | | |

Appendix 'B'

WNH Approved Meter Bases

Revision 3



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-24SCALE:
NTSREV.
1DWG. NO.
APPENDIX BTITLE: **WNH APPROVED METER BASES****SINGLE POSITION METER BASE SELECTION TABLE**

| SERVICE VOLTAGE (PHASE/WIRE) | SERVICE AMPERAGE | SOCKET TYPE | ANSI FORM TYPE | APPROVED MODELS |
|---|------------------|-----------------------|----------------|---|
| 120/240V (1PH 3W) UNDERGROUND SERVICE | <=200A | 4 JAW | FORM 2S | <u>MICRO ELECTRIC</u> : BS2-TCV, BS2-TV <u>HYDEL</u> : EK400RO, EK400TO <u>EATON</u> : LM2, LU2 |
| 120/240V (1PH 3W) OVERHEAD SERVICE | <=200A | 4 JAW | FORM 2S | ANY 200A CSA APPROVED MODEL |
| 120/240V (1PH 3W) | 400A | 5 JAW (NOTES 1, 2) | FORM 3S | <u>HYDEL</u> : CT4-3 <u>EATON</u> : TCC5-3 |
| 120/240V CENTRAL METERED SERVICE (1PH 3W) | <=600A | 5 JAW (NOTES 1, 2) | FORM 3S | <u>MICRO ELECTRIC</u> : CL5-V <u>HYDEL</u> : CTS459PW <u>EATON</u> : TCC5-0 |
| 120/208V NETWORK SERVICE (2PH 3W) | <=200A | 5 JAW (NOTE 1) | FORM 12S | ANY CSA APPROVED MODEL |
| 120/208V (3PH 4W) | <=200A | 7 JAW | FORM 16S | ANY CSA APPROVED MODEL |
| 347/600V (3PH 4W) | <=200A | 7 JAW | FORM 16S | ANY CSA APPROVED MODEL |
| 120/208V OR 347/600V (3PH 4W) | >200A | 13 JAW | FORM 9S | <u>EATON</u> : TSU13 <u>HYDEL</u> : CTS130PW |
| 600V (3PH 3W) | <=200A | 7 JAW (NOTES 3, 4) | FORM 16S | ANY CSA APPROVED MODEL |

MULTI POSITION METER BASE SELECTION TABLE

| SERVICE VOLTAGE (PHASE/WIRE) | SERVICE AMPERAGE | SOCKET TYPE | ANSI FORM TYPE | APPROVED MODELS |
|---|---------------------|-----------------------|----------------|--|
| 120/240V (1PH 3W) UNDERGROUND SERVICE | <=200A PER POSITION | 4 JAW (NOTES 5, 6) | FORM 2S | <u>MICRO ELECTRIC</u> : BDA2-V, S42-V, BS43-V <u>HYDEL</u> : HC22R, H23R, HC42R, HC43R <u>EATON</u> : 2K2, 3K2, 2K4, 3K4 |
| 120/240V (1PH 3W) OVERHEAD SERVICE | <=200A PER POSITION | 4 JAW (NOTE 6) | FORM 2S | ANY CSA APPROVED MODEL |

- ① 5TH JAW REQUIRED IN THE 9 O'CLOCK POSITION
- ② BY-PASS DEVICE REQUIRED ON LEFT SIDE JAWS
- ③ LEGACY SERVICE VOLTAGE. SEE WNH CONDITIONS OF SERVICE FOR STANDARD VOLTAGES AVAILABLE
- ④ 600V 3PH 3W SERVICES USING A 7 JAW SOCKET ARE TO HAVE THE 5TH JAW IN THE 6 O'CLOCK POSITION
- ⑤ MAXIMUM NUMBER OF METER BASE POSITIONS FOR AN UNDERGROUND SERVICE IS THREE
- ⑥ ALL MULTI POSITION METER BASES REQUIRE A BLANK CONNECTION COMPARTMENT

| REV. | DESCRIPTION | DATE | INITIALS |
|------|--------------------|------------|----------|
| 1 | APPENDIX B CREATED | 03/24/2021 | BD |
| | | | |



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

Appendix 'C'

WNH Approved Combination Transfer Switch Meter Bases & Plug-In Transfer Devices



WATERLOO NORTH HYDRO INC.

DATE:
2021-03-24SCALE:
NTSREV.
1DWG. NO.
APPENDIX CTITLE: **WNH APPROVED COMBINATION TRANSFER SWITCH METER BASES & PLUG-IN
TRANSFER DEVICES****COMBINATION TRANSFER SWITCH METER BASES (SECTION 3.8.16)**

| SERVICE VOLTAGE (PHASE/WIRE) | SERVICE AMPERAGE | SOCKET TYPE | ANSI FORM TYPE | APPROVED MODELS |
|------------------------------------|---------------------|----------------|-------------------|----------------------------|
| 120/240V (1PH 3W) | <=200A | 4 JAW | FORM 2S | <u>EATON</u> : EGSC200AMSE |

PLUG IN TRANSFER DEVICES (SECTION 3.8.15)

| SERVICE VOLTAGE (PHASE/WIRE) | SERVICE AMPERAGE | SOCKET TYPE | ANSI FORM TYPE | APPROVED MODELS |
|------------------------------------|---------------------|----------------|-------------------|--|
| 120/240V (1PH 3W) | <=200A | 4 JAW | FORM 2S | <u>GENERLINK</u> : MA23-N, MA23-S, MA24-N, MA24-S |

| REV. | DESCRIPTION | DATE | INITIALS |
|------|--------------------|------------|----------|
| 1 | APPENDIX C CREATED | 03/24/2021 | BD |
| | | | |



Waterloo North Hydro Inc.
ECRA/ESA License # 7004206

METERING SPECIFICATIONS

526 Country Squire Road
Waterloo ON, N2J 4G8
Tel: 519-888-5557
Fax: 519-885-4524
eclerk@wnhydro.com

Appendix 'D' Metering Pulse Output(s) Access Agreement

Appendix D: WNHI Metering Pulse Output(s) Access Agreement

This agreement between

Waterloo North Hydro Inc.
526 Country Squire Road,
Waterloo, ON N2J 4G8

hereafter referred to as WNHI

and

Customer's Business Name: _____

Address: _____

City: _____

Province/State: _____

Postal/Zip Code: _____

carrying out business at

Customer's Service Address: _____

City: _____

Province: Ontario

Postal Code: _____

WNHI. Account #: _____

carrying out business as

Business Name: _____

hereafter referred to as the Customer,

shall define the relationship between WNHI and the Customer and its Assigned Third Party, if applicable, with respect to provision of isolated, KYZ metering pulse output(s). For the purposes of this agreement, the term 'Assigned Third Party' is meant to include Retailers.

Pursuant to Section 11.1 (Provision of Current Usage Data to Retailers) and Section 11.2 (Provision of Current Usage Data to Customers) of the Retail Settlement Code, WNHI agrees to provide isolated, KYZ metering pulse output(s) from WNHI's meter at the Customer's above-noted service address under the following conditions:

- The Customer and Assigned Third Party accepts that the availability of KYZ metering pulse output(s) is subject to termination with notice by WNHI where practicable due to the planned elimination of this technology. Where the purchase of special meter(s) is necessary to accommodate the Customers or Third Party's requirements all reasonable related costs will be borne by the Customer.
- The Customer or Assigned Third Party must request a quotation for the total cost of installing equipment to provide the necessary KYZ pulses. This will include, but is not limited to: isolation relays to electrically protect WNHI metering equipment, labour, truck time, terminal

strips, isolation relay cover and separate pulse output enclosure. Also, the Customer or Assigned Third Party must supply an Electrical Safety Authority (ESA) inspected 120 VAC duplex receptacle within the existing meter cabinet. This receptacle should be on a separate, fused circuit to avoid tripping due to other devices on the line. Once this quotation is done and accepted by the Customer or Assigned Third Party, a purchase order must be issued before WNHI will schedule the work. Please allow 6-8 weeks after receipt of the purchase order for work to be completed due to labour scheduling and material lead times.

- WNHI will supply either: Watt-hour, Watt-hour/VA-hour or Watt-hour/VAR-hour KYZ pulses depending on the outputs available from the WNHI meter already installed or to be installed at the Customer's metering installation.
- If it is deemed that WNHI's metering installation is somehow compromised by any unforeseen event or circumstances not present at this time, the Customer's/Assigned Third Party's access to the isolated, KYZ metering pulse outputs may be suspended by WNHI.
- The Customer shall pay the reasonable cost of any software, hardware or other services required for the Customer/Assigned Third Party to obtain isolated, KYZ metering pulse output access to the WNHI meter.
- The Customer shall bear any cost incurred by WNHI to correct problems caused by the Customer's/Assigned Third Party's access to the isolated, KYZ metering pulse output(s). This includes, but is not limited to: trouble calls to repair/maintain the isolated, metering pulse output(s) connections and equipment, replacement of any parts/equipment required to sustain the metering pulse output(s), and additional labour required to re-connect and test the isolated, metering pulse output(s) during a required meter change.
- If the Customer assigns his or her right to isolated, KYZ metering pulse output(s) access to any Assigned Third Party, the Customer shall remain responsible for the action of the Assigned Third Party. Also, the Customer must supply the following contact information regarding the Assigned Third Party to WNHI in the space below:

(If applicable, please complete. For more than one Assigned Third Party please attach additional information for each to the end of this Agreement.)

Assigned Third Party Information

Business Name: _____

Contact Name: _____

Address: _____

City: _____ Province/State: _____

Postal/Zip Code: _____ Retailer License #: _____

Phone: _____ Fax: _____

E-mail: _____

- If the Customer wishes to withdraw the right from any Assigned Third Party, it must do so in writing to WNHI so that any other affected parties can be notified.
- The data obtained by the Customer or its Assigned Third Party via the isolated KYZ metering pulse output(s) from the meter is to be considered raw and without any additional validation, estimation or editing applied to it by WNHI. As such, it is expected that this data may vary on occasion from that supplied by WNHI's billing system, or any other source of settlement-ready interval metering data. If a discrepancy occurs between any data presented to the Customer and that presented by WNHI's actual billing, WNHI's actual billing must be used as correct values. WNHI does not assume any liability for any damages or losses that may occur as a result of further use of raw interval data.

This agreement shall be applicable to all successors and assigns and shall not be re-assigned without written notification of WNHI.

Contact with the Customer regarding this agreement will be with the person(s) listed below with respect to this interval metering installation for the purposes of read-only access. The Primary Contact will be responsible for maintaining the communication link at the interval meter location.

Customer Contact Information

(Required) Primary Contact Name: _____

Address: _____

City: _____ Province/State: _____

Postal/Zip Code: _____ Retailer License #: _____

Phone: _____ Fax: _____

E-mail: _____

(Optional) Alternate Contact Name: _____

Address: _____

City: _____ Province/State: _____

Postal/Zip Code: _____ Retailer License #: _____

Phone: _____ Fax: _____

E-mail: _____

For the Customer, I have the authority to bind the company.

Signature: _____

Name: _____

Position: _____

Date: _____

Address: _____

City: _____ Province/State: _____

Postal/Zip Code: _____

Phone: _____ Fax: _____

E-mail: _____

Contact for Waterloo North Hydro Inc. will be:

Name: Aaron Melo
Billing & Settlement Supervisor
Phone: (519) 888-5598
Fax: (519) 746-0133
E-mail: amelo@wnhydro.com

Once the completed and signed Agreement is mailed or faxed to WNHI, we will supply a detailed summary of the metering information required to enable the Customer/Assigned Third Party to have isolated access to this metering installation.